_							
\vdash	A	В	C	D	Е	F	G
	I. Bocal		Original bocal, Gambette1 No				
	dia reed end		inside diameter of reed end of bocal				
3	bocal string length (0, 1)		length of bocal inserted into receiver				
4	metal bocal length top (0, 1)		meas. along top of bocal				
5	metal bocal length bot (0, 1)		meas. along bottom of bocal				
6	dia wj end		inside diameter of bocal				
7							
8	bocal logic	2	if bocal logic = $0 \Rightarrow$ bocal is choke; if bocal logic = $1 \Rightarrow$ choke in wing joint calc; if boc	al $logic = 2 =$	> no bo	ocal	
9							
10							
11							
12							
	II. Wing Joint Lengths		bocal receiver: Gambette1 no, where bocal set is very worn out, istr. Looks as if it was				
14	choke bore dia.	10	logic 1; bore diameter of choke; logic 0; either diameter bocal bottom or beginning of b		or rece	eiver	
15	receiver length (1, 0) (formally choke length)	55	logic 1; length of choke from top of wing joint; logic 0; length of receiver (same as strin	ig length)			
16	wing joint length	499	total wing joint length, including tenon and socket				
17	tenon length	46.8	tenon length				
18		247	Gambette1 Wing tenon has been replaced				
19	wj f2	217	dist top of wing to where tone hole enters bore [not at the center of the tone hole]				
	wj e	290					
21	wj d	340					
22	D	16.1					
23	Bore dia. Bottom of wing joint	16.4	Need to Average, usally oval; Gambette1 yes				
24	Bore dia. top of boot joint small side	15.9					
25	Bore dia. top of boot joint large side	24.4					
26	TIT Poot Longths						
	III. Boot Lengths	- 1	logic=> if hi logic = 0 => plug removed: if hi logic = 1				
	bj logic	100	logic=> if bj logic = 0 => plug removed; if bj logic = 1 => plug cannot be removed				
30	bj c	108	dist from top of boot to where topmost tone hole enter bore [not at center of tone hole]				
	bj b bj a	168 208					
32	υj α	200					
33	bjstotal [Needed for both boot logics]	447	total length of hoot, include socket, along the small have side				
33	bjltotal [Needed for both boot logics]	447	total length of boot, include socket, along the small bore side total length of boot, include socket, along large bore side				
35	plug small [Need for logic 0 only]	0	plug thickness, large bore side				
36	plug large [Need for logic 0 only]	0	plug thickness, small bore side				
37	plag large [Need for logic o only]		ping theritess, shall bore side				
38	boots [Needed for both boot logics]	409	hook length along s bore => bjs-septum length = boot - septum <= calc the septum				
39	bootl [Needed for both boot logics]	409	hook length along I bore => bjl-septum length = boot - septum <= calc the septum				
40							
41	boots bottom [Needed for both boot logics]	16	use hook, dist of bore [dist on stick plus 7mm, diff between hook and bot of stick] 9 + 7	7=16			
42	bootl bottom [Needed for both boot logics]	16	use hook, dist of bore [same as boots bot except tenon depth will be different]				-
43			·				
44	extreme bore [Needed for logic 1 only]	42.2	Outside dia of plug [measured] = small bore dia + large bore dia + the septum width				
45							
46	septum length exp [Need for logic 0 only]	0	dist. from very bottom of boot to septum [point between the large and small bore]				
47	septum length calc - do not imput value	38	dist. From very bottom of boot to spetum [bjl - bootl]	do not imput			
48	septum length - do not imput value	38	if bj logic = 0 => septum = septum exp; if bj logic = 1 => septum = septum calc	do not imput	value		
49							
50	sbore dia sep* [Needed for both boot logics]	18.9	septum small bore dia [assume = Ibore dia sep]				
51	Ibore dia sep* [Needed for both boot logics]	19.3	septum large bore dia [assume = sbore dia sep] [mesure if cork can be removed; for Lo	ogic 0]			
52	sep width exp [Need for logic 0 only]	0	septum width; direct measurement if remove plug				
53	sep width calc - do not imput value	4	septum width; calc. => extreme bore - sbore - lbore	do not imput			
54	sep width - do not imput value	4	if bj logic = $0 \Rightarrow$ sep width = sep width exp; if bj logic = $1 \Rightarrow$ sep width = sep width c	do not imput	value		
55	1.	247					
56	bj g	347	dist from top of boot (socket) to where G hole enters bore [not at cent of tone hole]				
57	bj f1	144	dist from top of boot (socket) to where F1 hole enters bore [not at cent of tone hole]				
58							
59 60						-	-
61							
62							
63	IV. Tone Hole Diameters						
64	f2	5.3					-
65	e	5.9					
66	d	5.2					
67							
68	С	7					
69	b	6.3					
70	a	5.4					
71	g	9					
72 73	f1	9.2					
73							
74 75	e1	9.1	e1 tone hole dia, on long joint [need to average NS and EW dias, NS usually greater]				
75	d1	9.3	Gambette1 oblong 8.9 x 9.6; d1 tone hole dia, on long joint [need to average NS and E	W dias, NS us	ually gr	eater	1
76	<u>c1</u>	13.3	c1 tone hole dia, on long joint [need to average NS and EW dias, NS usually greater]				
77							
78							
79							
80							
81	V. Tone Hole Depths						
83	f2	34					
84	12 e	28.2					
85	d	33.5	D tone hole drilled at fairly extreme angle				
86		33.3					
87	С	21.4					
88	b	25.3					
89	a	25.8					
90	9	12.2	meas along bot tone hole wall [north wall, toward reed,tone hole usually at angle]				
91	f1	19.2	meas along east side tone hole wall [north wall, toward reed,t hole usually at angle]				
92							
93	el el	8.4	e1 tone hole depth;meas east/west with deapth gauge [at center, or shortest dist]				

_				_	_	- 1	
- 1	A	B 0.4	C	D	Е	F	G
	d1	8.4	d1 tone hole depth; meas east/west with deapth gauge [at center, or shortest dist]				
95	c1	8.6	c1 tone hole depth; meas east/west with deapth gauge [at center, or shortest dist]				
96 97							
98							
98							
100							
	VI. Long Joint		Gambette1 a table along long joint				
	lg_length	598	total length of long joint				
	lg_tenon_bot	47.6	length bottom tenon on long joint [tenon going into boot joint]				
	lj_bot_bore	23.9	Gambette1 OOR 24.4 x 23.5; long joint bottom tenon bore diameter [tenon going into	hoot joint1			
	lj_top_bore	32.9	long joint top tenon bore diameter [tenon going into bell]	5000 joinej			
	lg_tenon_top	44.8	length top tenon on long joint [tenon going into bell]				
	e1 distance	55	dist long joint tenon to e1 [from bot of tenon to where tone hole enters bore]				
	d1 distance	254	dist long joint tenon to d1 [from bot of tenon to where tone hole enters bore]				
	c1 distance	471	dist long joint tenon to c1 [from bot of tenon to where tone hole enters bore]				
110							
111							
112							
113							
114							
115	VII. Bore diameters at Tone Holes						
116	f2	12					
117	e	13.1					
118	d	13.5					
119							
120	с	16.6					
121	b	17.2					
122	a	17.5					
123	g	20.3					
	f1	22.9					
125							
126	e1	25.2	e1 tone hole bore diameter on long joint				
	d1	28.6	d1 tone hole bore diameter on long joint				
128	c1	32	c1 tone hole bore diameter on long joint				
129							
130							
131							
132							
133							
	VIII. Bell		Gambette1 no tone hole in the bell				
	bell logic	1	If bell_logic = 0 => normal conical bore; if bell_logic = 1 => inverted concial bore; if bell_logic = 1 => inv	ell_logic = 2 =	:> bell	expar	nsion
136	bell_length (0, 1, 2)	323	total length of bell [lines 141 + 144 = line 136]				
137	bell_bot_bore (0, 1, 2)	32.3	dia bore at the bottom of bell [end with socket]				
138	bell_top_bore 0, (1, 0, 2)	31.1	dia bore at the top of bell [where low Bb exits]				
139	bell_center_bore (only for logic 2)		dia bore at max center of expansion				
140	bell_wall (only for logic 2)		bell wall thickness, Just for David	101			
	bell_bot_bore_expansion (only for logic 2)		dist of bottom to maxium of expansion [including bell socket length,if bell logic=0 =>10	10]			
142	Outside diameter of wood at expansion	45	Just for David				
143	bell_tenon (0, 1, 0, 2) bell_expansion_length (only for logic 2)	45	bell socket length				
	Bellflg	41	distance of maxium expansion to top of bell [where Bb exits]				
146	beiling	41					
147							
	IX. PITCH						
	pitch	415	input the historical pitch of the bassoon, must input value, best guess				
150	freq_init	380	Initial frequency range variable				
	Delta frequency	2	frequency increment parameter				
152	Number of frequencies	60	number of frequencies to scan for min chi sq				
	Frequency adjust	1.05	frequency adjustment parameter				
	X. Title						
	title		Bassoon Calculation: Gambette1-O-Watel234-Wg1-WOB-DNM				
156							
157			Notes on long joint bore: Gambette1 very OOR in places				
158			Notes on boot joint bore: Gambette1 small side OOR				
	XI. Bore Diameter Locations		Notes on wing join bore: Gambette1 normal				
160		21	Number of diameters				
	Bell Bore	10	Initial bore diameter				
	32.3mm diameter at socket	0	dist1; measured from the bottom of the wing joint- 10mm				1
	32mm rod 150mm from socket	345	dist2; measured from the bottom of the wing joint- 11mm				1
	31.5mm rod 195mm from socket	287	dist3; measured from the bottom of the wing joint- 12mm				1
165	31.1mm diameter at bell end	211	dist4; measured from the bottom of the wing joint- 13mm				1
166		78	dist5; measured from the bottom of the wing joint- 14mm	Dotte:	10.4		1
167		17		Bottom wing	16.4		1
168		65	dist7; measured from the top of the bootjoint - small bore side- 16mm	top boot sma	15.9		2
169		155		top boot larg	24.4		2
170		350	dist9; measured from the top of the bootjoint - small bore side- 18mm	abara di	10.0		2
171 172		0 375	dist10; measured from the top of the bootjoint - large bore side- 19mm	sbore dia ser Ibore dia sep	18.9		3
173		3/5	dist11; measured from the top of the bootjoint - large bore side- 20mm Gambette1 OOR; dist12; measured from the top of the bootjoint - large bore side- 21mi		19.3		3
174		205	dist13; measured from the top of the bootjoint - large bore side- 21ml				2
175		144	dist13; measured from the top of the bootjoint - large bore side- 22mm dist14; measured from the top of the bootjoint - large bore side- 23mm				<u>3</u>
176		62	dist15; measured from the top of the boot joint - large bore side- 23mm dist15; measured from the top of the boot joint- large bore side- 24mm	lj_bot_bore	23.9		2
177		552	dist15; measured from the top of the long joint- large bore side- 24mm dist16; measured from the top of the long joint- 25mm	ij_bot_bore	23.3	-	
178		495	dist17; measured from the top of the long joint- 25mm				- 4
179		445	dist18; measured from the top of the long joint- 27mm				4
180		380	dist19; measured from the top of the long joint- 28mm				4
181		310	dist20; measured from the top of the long joint- 29mm				4
182		238	dist21; measured from the top of the long joint- 30mm				- 1
183		170	dist22; measured from the top of the long joint- 31mm				4
184		119		lj top bore	32.9		4
1 1 1 1 1		112	and the first and the first top of the form point of the delities				